

Product Datasheet uvex 2 6502.1-4 S3 SRC

**UVEX ARBEITSSCHUTZ GmbH, Würzburger Str. 181-189, D-90766 Fürth****Product information**

- Sporty, multifunctional safety shoes
- Extremely light and flexible
- The latest generation of 100% metal-free uvex xenova® toe cap. Compact design, anatomical shape, good side and ankle twist stability, no thermal conductivity and antimagnetic properties
- Metal-free, penetration-resistance insole in accordance with the latest standard, which does not impact shoe flexibility
- Made with new high-performance technology for exceptional wearer comfort
- uvex climazone technology for optimum comfort
- Water-repellent, breathable and extremely soft leather upper
- Distance mesh lining provides optimum breathability
- Individually adjustable due to elastic laces with quick-lock mechanism; normal laces also provided (6502 only)
- Virtually seam-free construction to eliminate pressure points
- Removable comfort insole, antistatic, with moisture control system and additional shock absorption in the heel and at the front of the foot
- Soft, padded collar and padded tongue
- Injection-moulded polyurethane scuffcap to protect upper leather on toe cap and significantly extend resistance time

	<ul style="list-style-type: none">• Meets ESD requirements: resistance to ground < 35 megaohm• Certified with uvex medicare for individual, orthopaedic inlay soles and individual adjustments of the sole unit such as overall increase, inside and outside increase and other solutions																				
Outsole	<ul style="list-style-type: none">• Lightweight two-layer insole with excellent shock absorption characteristics and outstanding slip resistance, free of lacquer wetting inhibitors such as silicones and phthalates (plasticisers)• Multilayer shock absorption system comprising double-layer uvex 2 PU outsole and comfortable insole, shock absorption in the front and heel: all this protects the musculoskeletal system, even over long periods of time• Optimised ankle protection to ensure safety when working on ladders• Particularly abrasion-resistant TPU sections ensure secure stepping and rolling of foot, which helps prevent accidents• Rugged, self-cleaning sole ridges ensures maximum grip for demanding applications on uneven or dirty floors (SRC labelling).																				
Technical data	<table><tr><td>Art.-no.</td><td>6502.1</td><td>.2</td><td>.3</td><td>.4</td></tr><tr><td>Width</td><td>10</td><td>11</td><td>12</td><td>14</td></tr><tr><td>Standard</td><td colspan="4">EN ISO 20345:2011 S3 SRC</td></tr><tr><td>Size</td><td colspan="4">35 – 52</td></tr></table>	Art.-no.	6502.1	.2	.3	.4	Width	10	11	12	14	Standard	EN ISO 20345:2011 S3 SRC				Size	35 – 52			
Art.-no.	6502.1	.2	.3	.4																	
Width	10	11	12	14																	
Standard	EN ISO 20345:2011 S3 SRC																				
Size	35 – 52																				
Accessories	<p><i>uvex 1 comfortable climatic insole</i> (article no.: 9534.7-9 + .0)</p> <ul style="list-style-type: none">• Provides the foot with exceptional, full-surface shock absorption and ensures comfort in high-strain zones• Ultra breathable and moisture-absorbing materials• Shock absorption zones that assist natural movement• Non-irritating, comfortable surface structure <p><i>Laces</i></p> <ul style="list-style-type: none">• Black (article no.: 9599.9 11)• Elastic laces (article no.: 9591.000)																				