



**GENESIS  
7X104**

**S1P SRC  
EN ISO 20345:2011  
36 to 47**

**Low shoe  
Urban sport**



## DOMINUS

**3D Lining**

**Light PLUS**

**COMFORT PLUS**

**FLEX system<sup>®</sup>  
ZERO**

**metal  
FREE**

- ⌚ Low urban sport safety shoe, grey colour. PU toe protection in front.
- ⌚ Suede leather upper Thickness 1,8 / 2,0. Fresh textile insert on the side.
- ⌚ **3D.LINING<sup>®</sup>** in three-ply material for improved evacuation of moisture to the exterior, high breathability and fast-drying.
- ⌚ Vamp lining in non-woven fabric. Resists abrasion and acid perspiration.
- ⌚ Padded collar. Provides comfort to the ankle-bones and protects the Achilles tendon.
- ⌚ Fastened by lacing. Laces 120 cm.
- ⌚ Padded tongue to provide better protection to the instep, combined with two side gussets to prevent grit from entering the shoe.
- ⌚ Complete **COMFORT PLUS<sup>®</sup>** inlay, antistatic and anatomically shaped in flexible polyurethane covered in breathable, absorbent fabric.
- ⌚ Stab-proof non-metallic **FLEX-SYSTEM<sup>®</sup>** liner : total protection of the sole of the foot.
- ⌚ **LIGHT-PLUS<sup>®</sup>** protective toecap in synthetic material offering protection from an impact of 200 J.

### Slip resistance tests results

EN Standard : EN ISO 20345 : 2011

**Requirement SRC (SRA+SRB)**

**SRA** Test ground : ceramic / lubricant : water and detergent

On flat **0,44** (>0,32) – On the heel **0,37** (>0,28)

**SRB** Test ground steel / lubricant : glycerine

On flat **0,19** (>0,18) – On the heel: **0,15** (>0,13)

**W-Tech Wrapping Technology** sole in PU dual density :

- Resists oils and hydrocarbons .
- Slim, streamlined profile rising towards the toes.
- Absorption of heel impact > 20 joules
- Wrap-around profile for better stability when walking



Weight	Gross Weight (42) : 1272 g / Net Weight (42) : 1054 g			
Size	36 to 39	40 to 41	42 to 45	46 to 47
Packaging	5 pairs	10 pairs		5 pairs
Box (mm)	306 x 192 x 114		340 x 210 x 133	
Cartons (mm)	585 x 199 x 315	585 x 395 x 315	680 x 425 x 350	680 x 215 x 350